

**Waiver:**

This data sheet is for guidance only and must not be used for proper working drawings. Please contact supplier for particular details before proceeding. Owing to our policy of continual improvement we reserve the right to alter specifications and dimensions without prior notice.

# Ideal Lift 3 Machine Room-Less



MRC

8 Person (630kg)

Travel: 15.4m max.  
Speed: 0.63m/s max.

Contact: 01837 659999

**Option: MRC-RM**  
Machine Room in Cabinet  
- Recess Mounted

Only available on the guide side on structure supported installations

An area of 810 wide x 725 deep, and a clear height of 2125mm should be available in front of the machinery cabinet for maintenance.

A MACHINERY CABINET supplied with the lift, is fitted in the shaft wall. A structural clear opening in front of the fire barrier is to have minimum dimensions of 850 wide x 400 deep x 2125 high. Further details may be found on builders work drawings.

† Note: Controller not fire certified. Fireproof barrier behind cabinet to be provided by builder

Part 'M' Bldg Regs:  
A clear landing  
1500mm wide x  
1500mm deep in  
front of lift doors should be provided for access by wheelchair users.

**Option: MRC-SM**  
Machine Room in Cabinet  
- Surface Mounted

An area of 810 wide x 725 deep, and a clear height of 2125mm should be available in front of the machinery cabinet for maintenance.

A MACHINERY CABINET, supplied with the lift, can be positioned on any side adjacent to, or remotely within 8m of the lift well. The external dimensions of the cabinet are 810 wide x 365 deep and 2100 high. Further details may be found on builders work drawings.

Part 'M' Bldg Regs:  
A clear landing  
1500mm wide x  
1500mm deep in  
front of lift doors should be provided for access by wheelchair users.

\*\* See datasheet 8.13.3 for information on well dimensions, imposed loads and general details of 8 person lifts.



Machine Room-Less  
MRC  
**8.14.3**  
17/10/06